

Arctigo ISD

Benefits

- Application based air cooler design to secure product quality
- Advanced product selection software available
- Heavy duty coil & casing materials, resulting in a long operational product life
- Exceptionally wide & versatile cooler range
- Eurovent certified performance
- Easy installation
- Energy efficiency
- Low defrost frequency thanks to square tube pitch configuration
- Low total cost of ownership
- Two-year product guarantee
- Easy access to on-line product information

General information & application

Arctigo ISD is a wide and flexible range of single discharge industrial air coolers for both cooling and freezing applications in medium to large cold rooms. This industrial air cooler line has been designed using the Helpman® heritage, to keep fresh and frozen goods refrigerated from +10 to -40 °C, with either high or low humidity content.

The Arctigo range offers a wide variety of cooler configurations and a long list of options, always allowing to select the best model to suit all applications in industrial refrigeration installations. Arctigo air cooler models are available for dedicated applications such as agricultural storage, airlock application or shock cooling.

Refrigerants	HFC, ammonia, brine, CO ₂
Capacities (SC2)	3 up to 240 kW
Air volume	3,000 up to 130,000 m ³ /h

Standard configuration

- Finned coil:
 - 10 coil block modules
 - 3, 4, 6, 8 or 10 tube rows deep
 - Tubing ø 5/8 "Cu ripple fin, smooth Cu tubing for brine or smooth stainless steel
 - Tube pitch 50 mm square
 - Corrugated Alu-fins
 - Fin spacings 4, 5, 6, 7, 8, 10 and 12 mm
- 1 to 6 fans, ø 400 mm up to ø 910 mm, drawing through the coil. Power supply 400/50-60/3 or 230/50-60/1 (for ø 400 and 450 mm), two noise levels (Δ/Y connections). AC/EC fan motors with dynamically and statically balanced external rotors, manufactured in accordance with VDE 0530/12.84 IP54 class F. Integrated thermo contacts (Clickson) provide reliable protection against thermal overload.
- Corrosion resistant materials: coil frame and casing pre-galvanized sheet steel, epoxy coated RAL 9003. All fixing materials stainless steel.
- Hinged side panels and drip tray, drain(s) 1½" BSP ext.
- Fitted with schrader valve on the suction connection for testing purposes.
- Refrigerant connections right or left (L=default).
- Sufficient room for fitting the expansion valve inside.
- Suitable for dry expansion or pumped system.
- Stickers indicate fan direction and refrigerant in/out.




Arctigo ISD

Industrial air coolers single discharge

Options

- Connection box (CB)
- Connection box with single switch for all fans (CB1)
- Shut up sock (S)
- Sock Ring (SR)
- Electric defrost systems:
 - Electric defrost in driptray + hot gas in coil (E1)
 - Electric defrost heavy (E2)
 - Electric defrost light (E4)
- Hotgas defrost systems:
 - Hotgas defrost (HG)
 - Hotgas defrost, connected (HGC)
- Hot water defrost (HW)
- Stainless steel casing and coil frame (SSC)
Standard materials for underplate (aluminium) and fan grid (black painted steel)
- Alternative fin materials (SWR / EP)
- Dual fin spacing (DF)



Design pressure

Refrigerant	Design pressure
HFC	33 bar
Ammonia	30 bar
CO ₂	33-40-60 bar
Brine	10 bar

Each heat exchanger is leak tested with dry air and finally supplied with a nitrogen pre-charge.

Selection

Selection and pricing is to be performed with our online air heat exchanger selection software **Plair**.

Selection output includes all relevant technical data and dimensional drawings.

Certifications

The Alfa LU-VE quality system is in accordance with ISO 9001. All products are manufactured according to PED regulations. Eurovent certified performance applies to models included in the scope of the programme.



31562448EN 2204

Alfa LU-VE is a trademark registered and owned by LU-VE Group.
Alfa LU-VE reserves the right to change specifications without prior notification.

- On/off switch (SW)
- Motorized defrost damper
- Threaded connections (T) - *for brine models*
- Top connections (AVA) - *for brine models*
- Slip-on flanges aluminium PN16 for copper tubes models or stainless steel PN16 stainless steel tubes models (F) - *for brine models*
- Fan casing 90° (FC1)
- Fan casing 45° (FC2)
- Suction hood 90° (H1)
- Suction hood 45° (H2)
- Insulated suction hood 90° (IH1)
- Insulated suction hood 45° (IH2)
- Insulated drip tray (I2)
- Mounting feet (MF)
- Fan ring heater (FRH)
- Streamer (ST)

Code description

ISD	7	1	1	-	2	0	S	A	C	E	A	3	3	AL	7	-	AB	5	4	-	AB	D	-	L	FRH
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19							

- 1 Arctigo industrial air cooler single discharge - air direction draw-through
- 2 Fan diameter (40=400, 45=450, 50=500, 63=630, 71=710, 80=800, 91=910 mm)
- 3 Number of fans (1 to 6)
- 4 Tubes per row
- 5 Coil module (blank=standard coil module, S=short coil module)
- 6 Tube rows code (A=3 B=4 C=6 D=8 E=10)
- 7 Tube material (C=copper, S=stainless steel)
- 8 Application (E=direct expansion, PB=pumped bottom feed, PT=pumped top feed, blank for brine units)
- 9 Refrigerant system (H=HFC, A=ammonia, W=brine, X=CO₂)
- 10 Maximum working pressure
- 11 Fin material (AL=aluminium, EP=precoated aluminium, SWR=sea water resistant aluminium)
- 12 Fin spacing (4=4.0, 5=5.0, 6=6.0, 7=7.0, 8=8.0, 0=10, 2=12 mm)
- 13 Number of circuits (2 digits)
- 14 Capillary diameter (1 digit: for brine and pump there is X, for DX there is 4, 5 or 6)
- 15 Orifice diameter (mm, only for NH₃ units)
- 16 Fan motor code (2 digits)
- 17 Fan digit (D or Y for AC 3ph, S for AC 1ph, E for EC)
- 18 Refrigerant connection side (L=left, R=right - fan side view)
- 19 Options